

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): GRS-CQ4.0Pd/NhH-E							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	5	kW	Seasonal space heating energy efficiency	$\eta_s$	128	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = -7\text{ °C}$	Pdh	4.0	kW	$T_j = -7\text{ °C}$	COPd	2.03	-
Degradation co-efficient (**)	Cdh	0.99	-				
$T_j = 2\text{ °C}$	Pdh	2.6	kW	$T_j = 2\text{ °C}$	COPd	3.27	-
Degradation co-efficient (**)	Cdh	0.97	-				
$T_j = 7\text{ °C}$	Pdh	2.3	kW	$T_j = 7\text{ °C}$	COPd	4.30	-
Degradation co-efficient (**)	Cdh	0.95	-				
$T_j = 12\text{ °C}$	Pdh	2.8	kW	$T_j = 12\text{ °C}$	COPd	6.00	-
Degradation co-efficient (**)	Cdh	0.95	-				
$T_j = \text{bivalent temperature}$	Pdh	4.0	kW	$T_j = \text{bivalent temperature}$	COPd	2.03	-
$T_j = \text{operation limit temperature}$	Pdh	3.8	kW	$T_j = \text{operation limit temperature}$	COPd	1.38	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	COPd	NA	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Psych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0.025	kW	Rated heat output (*)	P <sub>sup</sub>	1.2	kW
Thermostat-off mode	P <sub>TO</sub>	0.025	kW	Type of energy input	Electric		
Standby mode	P <sub>SB</sub>	0.025	kW				
Crankcase heater mode	P <sub>CK</sub>	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	3200	m <sup>3</sup> /h
Sound power level, indoors/outdoors	L <sub>WA</sub>	42/62	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m <sup>3</sup> /h
Annual energy consumption	Q <sub>HE</sub>	3152	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	107.5	%
Daily electricity consumption	Q <sub>elec</sub>	7.532	kWh	Daily fuel consumption	Q <sub>fuel</sub>	NA	kWh
Annual electricity consumption	AEC	1559	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): GRS-CQ4.0Pd/NhH-E							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Colder climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	3	kW	Seasonal space heating energy efficiency	$\eta_s$	95.1	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = -7\text{ °C}$	Pdh	1.9	kW	$T_j = -7\text{ °C}$	COPd	1.72	-
Degradation co-efficient (**)	Cdh	0.98	-				
$T_j = 2\text{ °C}$	Pdh	1.9	kW	$T_j = 2\text{ °C}$	COPd	3.41	-
Degradation co-efficient (**)	Cdh	0.96	-				
$T_j = 7\text{ °C}$	Pdh	2.6	kW	$T_j = 7\text{ °C}$	COPd	5.29	-
Degradation co-efficient (**)	Cdh	0.95	-				
$T_j = 12\text{ °C}$	Pdh	2.9	kW	$T_j = 12\text{ °C}$	COPd	6.71	-
Degradation co-efficient (**)	Cdh	0.94	-				
$T_j = \text{bivalent temperature}$	Pdh	2.7	kW	$T_j = \text{bivalent temperature}$	COPd	1.35	-
$T_j = \text{operation limit temperature}$	Pdh	2.3	kW	$T_j = \text{operation limit temperature}$	COPd	1.10	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20°C )	Pdh	2.7	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20°C )	COPd	1.35	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Psych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	$P_{OFF}$	0.025	kW	Rated heat output (*)	$P_{sup}$	0.7	kW
Thermostat-off mode	$P_{TO}$	0.025	kW	Type of energy input	Electric		
Standby mode	$P_{SB}$	0.025	kW				
Crankcase heater mode	$P_{CK}$	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	3200	m <sup>3</sup> / h
Sound power level, indoors/outdoors	$L_{WA}$	42/62	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m <sup>3</sup> / h
Annual energy consumption	$Q_{HE}$	3015	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	79.6	%
Daily electricity consumption	$Q_{elec}$	10.033	kWh	Daily fuel consumption	$Q_{fuel}$	NA	kWh
Annual electricity consumption	AEC	2104	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): GRS-CQ4.0Pd/NhH-E							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Warmer climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	4	kW	Seasonal space heating energy efficiency	$\eta_s$	153.6	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = -7\text{ °C}$	Pdh	NA	kW	$T_j = -7\text{ °C}$	COPd	NA	-
Degradation co-efficient (**)	Cdh	NA	-				
$T_j = 2\text{ °C}$	Pdh	4.2	kW	$T_j = 2\text{ °C}$	COPd	2.10	-
Degradation co-efficient (**)	Cdh	0.99	-				
$T_j = 7\text{ °C}$	Pdh	2.6	kW	$T_j = 7\text{ °C}$	COPd	3.40	-
Degradation co-efficient (**)	Cdh	0.97	-				
$T_j = 12\text{ °C}$	Pdh	2.7	kW	$T_j = 12\text{ °C}$	COPd	5.55	-
Degradation co-efficient (**)	Cdh	0.95	-				
$T_j = \text{bivalent temperature}$	Pdh	4.2	kW	$T_j = \text{bivalent temperature}$	COPd	2.10	-
$T_j = \text{operation limit temperature}$	Pdh	4.2	kW	$T_j = \text{operation limit temperature}$	COPd	2.10	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	COPd	NA	-
Bivalent temperature	Tbiv	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Psych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0.025	kW	Rated heat output (*)	P <sub>sup</sub>	0.0	kW
Thermostat-off mode	P <sub>TO</sub>	0.025	kW	Type of energy input	Electric		
Standby mode	P <sub>SB</sub>	0.025	kW				
Crankcase heater mode	P <sub>CK</sub>	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	3200	m <sup>3</sup> / h
Sound power level, indoors/outdoors	L <sub>WA</sub>	42/62	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m <sup>3</sup> / h
Annual energy consumption	Q <sub>HE</sub>	1365	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	111.0	%
Daily electricity consumption	Q <sub>elec</sub>	7.282	kWh	Daily fuel consumption	Q <sub>fuel</sub>	NA	kWh
Annual electricity consumption	AEC	1509	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): GRS-CQ4.0Pd/NhH-E							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	5	kW	Seasonal space heating energy efficiency	$\eta_s$	183.5	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = -7\text{ °C}$	Pdh	4.6	kW	$T_j = -7\text{ °C}$	COPd	3.23	-
Degradation co-efficient (**)	Cdh	0.98	-				
$T_j = 2\text{ °C}$	Pdh	2.9	kW	$T_j = 2\text{ °C}$	COPd	4.59	-
Degradation co-efficient (**)	Cdh	0.96	-				
$T_j = 7\text{ °C}$	Pdh	2.6	kW	$T_j = 7\text{ °C}$	COPd	6.39	-
Degradation co-efficient (**)	Cdh	0.94	-				
$T_j = 12\text{ °C}$	Pdh	2.8	kW	$T_j = 12\text{ °C}$	COPd	6.37	-
Degradation co-efficient (**)	Cdh	0.94	-				
$T_j = \text{bivalent temperature}$	Pdh	4.6	kW	$T_j = \text{bivalent temperature}$	COPd	3.23	-
$T_j = \text{operation limit temperature}$	Pdh	4.2	kW	$T_j = \text{operation limit temperature}$	COPd	2.56	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	COPd	NA	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Psych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	$P_{OFF}$	0.025	kW	Rated heat output (*)	$P_{sup}$	0.8	kW
Thermostat-off mode	$P_{TO}$	0.025	kW	Type of energy input	Electric		
Standby mode	$P_{SB}$	0.025	kW				
Crankcase heater mode	$P_{CK}$	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	3200	m <sup>3</sup> /h
Sound power level, indoors/outdoors	$L_{WA}$	42/62	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m <sup>3</sup> /h
Annual energy consumption	$Q_{HE}$	2216	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	107.5	%
Daily electricity consumption	$Q_{elec}$	7.532	kWh	Daily fuel consumption	$Q_{fuel}$	NA	kWh
Annual electricity consumption	AEC	1559	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): GRS-CQ4.0Pd/NhH-E							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Colder climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	4	kW	Seasonal space heating energy efficiency	$\eta_s$	145.1	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = -7\text{ °C}$	Pdh	2.4	kW	$T_j = -7\text{ °C}$	COPd	2.68	-
Degradation co-efficient (**)	Cdh	0.97	-				
$T_j = 2\text{ °C}$	Pdh	2.3	kW	$T_j = 2\text{ °C}$	COPd	5.34	-
Degradation co-efficient (**)	Cdh	0.94	-				
$T_j = 7\text{ °C}$	Pdh	2.7	kW	$T_j = 7\text{ °C}$	COPd	7.04	-
Degradation co-efficient (**)	Cdh	0.94	-				
$T_j = 12\text{ °C}$	Pdh	2.6	kW	$T_j = 12\text{ °C}$	COPd	6.90	-
Degradation co-efficient (**)	Cdh	0.93	-				
$T_j = \text{bivalent temperature}$	Pdh	3.1	kW	$T_j = \text{bivalent temperature}$	COPd	2.06	-
$T_j = \text{operation limit temperature}$	Pdh	2.8	kW	$T_j = \text{operation limit temperature}$	COPd	1.19	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	Pdh	3.1	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	COPd	2.03	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Psych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0.025	kW	Rated heat output (*)	P <sub>sup</sub>	1.3	kW
Thermostat-off mode	P <sub>TO</sub>	0.025	kW	Type of energy input	Electric		
Standby mode	P <sub>SB</sub>	0.025	kW				
Crankcase heater mode	P <sub>CK</sub>	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	3200	m <sup>3</sup> / h
Sound power level, indoors/outdoors	L <sub>WA</sub>	42/62	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m <sup>3</sup> / h
Annual energy consumption	Q <sub>HE</sub>	2663	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	79.6	%
Daily electricity consumption	Q <sub>elec</sub>	10.033	kWh	Daily fuel consumption	Q <sub>fuel</sub>	NA	kWh
Annual electricity consumption	AEC	2104	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): GRS-CQ4.0Pd/NhH-E							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	Y		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Warmer climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	5	kW	Seasonal space heating energy efficiency	$\eta_s$	232	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = -7\text{ °C}$	Pdh	NA	kW	$T_j = -7\text{ °C}$	COPd	NA	-
Degradation co-efficient (**)	Cdh	NA	-				
$T_j = 2\text{ °C}$	Pdh	4.8	kW	$T_j = 2\text{ °C}$	COPd	3.46	-
Degradation co-efficient (**)	Cdh	0.98	-				
$T_j = 7\text{ °C}$	Pdh	3.3	kW	$T_j = 7\text{ °C}$	COPd	5.57	-
Degradation co-efficient (**)	Cdh	0.96	-				
$T_j = 12\text{ °C}$	Pdh	2.9	kW	$T_j = 12\text{ °C}$	COPd	7.60	-
Degradation co-efficient (**)	Cdh	0.93	-				
$T_j = \text{bivalent temperature}$	Pdh	4.8	kW	$T_j = \text{bivalent temperature}$	COPd	3.46	-
$T_j = \text{operation limit temperature}$	Pdh	4.8	kW	$T_j = \text{operation limit temperature}$	COPd	3.46	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C )	COPd	NA	-
Bivalent temperature	Tbiv	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	P <sub>ych</sub>	NA	kW	Cycling interval efficiency	COP <sub>yc</sub>	NA	-
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0.025	kW	Rated heat output (*)	P <sub>sup</sub>	0.0	kW
Thermostat-off mode	P <sub>TO</sub>	0.025	kW	Type of energy input	Electric		
Standby mode	P <sub>SB</sub>	0.025	kW				
Crankcase heater mode	P <sub>CK</sub>	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	3200	m <sup>3</sup> / h
Sound power level, indoors/outdoors	L <sub>WA</sub>	42/62	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m <sup>3</sup> / h
Annual energy consumption	Q <sub>HE</sub>	1137	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	111.0	%
Daily electricity consumption	Q <sub>elec</sub>	7.282	kWh	Daily fuel consumption	Q <sub>fuel</sub>	NA	kWh
Annual electricity consumption	AEC	1509	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							





600081060200